



THERMOTEK PRO ACRYLIC PRIMER



DESCRIPTION

THERMOTEK PRO ACRYLIC PRIMER is manufactured with a water-based, high quality styrene-acrylic resin with excellent substrate adhesion. Use to prime and seal a wide variety of substrates. THERMOTEK PRO ACRYLIC PRIMER is compatible with all THERMOTEK PRO roof coating systems.

PROPERTIES:

Physical Property	Test Method (ASTM)	Value
VOC CONTENT	ASTM D-3960	<50 g/L
Viscosity, cps	ASTM D-2196	20 - 500
Density gr/ml (lb/gal)	ASTM D-1475	8.5 +/- 0.5
Appearance	Internal	LIQUID
Type	Internal	Water based product
Color	Internal	Aqueous white-transparent
Solids by weight, %	ASTM D-1644	39.14 +/- 1
Drying time for water resistance	ASTM D-1640	4 hours Drying time will increase depending on humidity
Total Dryingtime	ASTM D-1640	6 hours
PH	ASTM E-70	9,0 ± 0,5

BENEFITS

- Creates a permanently flexible and highly durable substrate seal
- Excellent alkali and corrosion resistance
- Blister and stain resistant
- Easy one-step application

SUBSTRATES

- Metal
- Sprayed Polyurethane Foam (SPF)
- Acrylic Roof Coatings
- Concrete
- Stucco
- Mortars
- Modified Bitumen Membranes (torch and self adhesive granulated finish membranes)
- Asphalt Build-up Surfaces
- Asphalt Roof Systems

APPLICATION TOOLS

3" paint brush, 3/8" nap woven roller and/or conventional or airless spray equipment (2000-3000 PSI, .041 Tip Size, 1-3GPM).

SURFACE PREPARATION

ALL ROOFS: If some areas hold excessive ponding water, they must be brought into conformance by installing proper drains. Roof surface must be clean, dry and free of any oil, grease, dirt and any other contaminants that could interfere with the proper adhesion to the substrate (pressure washing is recommended). If the roof contains grease spills, use mineral spirits and mop thoroughly. Any loose coating must be removed. Ensure the substrate is structurally sound, fully cured and dry. Perform adhesion test(s) (also known as Pull Test(s)) on the substrate. Pull Test(s): Apply a generous coat of THERMOTEK PRO ROOF COATING on the surface with a brush, a minimum of 6" (15 cm) long and 3" (7.5 cm) wide. Immediately embed a minimum of 1"-2" (2.5 cm - 5 cm) wide strip of THERMOTEK PRO ROOFING MESH while leaving at least 3" of the length of the mesh uncoated. Apply a second coat on top of the embedded strip section. Allow 48 hours to dry before trying the pull test. Pull the uncoated end of the mesh straight up. If the pull test exhibits good adhesion, continue with the application. If the test shows poor adhesion, redo the preparation and check that the correct system is being used.

METAL ROOFS: All rusted areas shall be mechanically abraded and corroded/deteriorated metal shall be replaced. A rust inhibitor should be used before applying THERMOTEK PRO PRIMER.

MODIFIED BITUMEN / ASPHALT BUILT UP ROOFS: Remove all the loose granules/sand with a brush and dispose of the waste (vacuum is an option for waste removal). To avoid yellowing of the top coat, use a yellowing inhibitor over the entire roof surface before applying THERMOTEK PRO ACRYLIC PRIMER. New asphalt shall be exposed to ambient conditions for 90 to 120 days before coating.

MIXING

THERMOTEK PRO ACRYLIC PRIMER must be mixed/ agitated for 3-5 minutes either by hand or with a mechanical mixer prior to use.

APPLICATION STEPS

Visit www.thermotekpro.com for short instructional videos



THERMOTEK PRO ACRYLIC PRIMER



1) PREP

- Complete proper surface preparation.

SMOOTH SURFACES: (i.e.: metal roofs): Dilute THERMOTEK PRO ACRYLIC PRIMER with water at a ratio of 1:3 (primer:water). Using a brush, roller or spray equipment, apply one (1) coat at a rate of 0.5 gal/100 sq. ft.

ROUGH SURFACES: (i.e.: granulated, concrete): DO NOT DILUTE. Using a brush, roller or spray equipment, apply one (1) coat of THERMOTEK PRO ACRYLIC PRIMER at a rate of 1 gal/100 sq. ft.

CURING TIME

3 hours. High humidity will result in longer drying times.

CLEAN UP

Clean application tools and equipment with clean water. DO NOT USE solvents.

PACKAGING

- BUCKET 0.90 GAL
- POUCH 33.8 oz (part of THERMOTEK PRO EASY AS 1-2-3 KIT)

STORAGE

The storage temperature should be greater than 41 °F (5 °C) and below 113 °F (45 °C). Keep only in the original container in a cool, well-ventilated and dry area, protected from the elements. Keep container tightly closed when not in use. Keep from freezing. Keep away from sources of ignition; no smoking. Protect from direct sunlight.

SHELF LIFE

Shelf life is 2 years.

FOR BEST PERFORMANCE

Do not apply at temperatures below 50 °F (10 °C) or above 104 °F (40 °C), or if cold weather, rain or fog is expected within 48 hours of application. Use a yellowing inhibitor over asphaltic systems before applying the THERMOTEK PRO ACRYLIC PRIMER to avoid yellowing.

COMPLIANCES / CERTIFICATIONS

- NATIONAL ROOFING CONTRACTORS ASSOCIATION (MEMBER)



NATIONAL
ROOFING
CONTRACTORS
ASSOCIATION
MEMBER



THERMOTEK PRO ACRYLIC PRIMER



LIMITED WARRANTY: Master Builders Solutions US warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide available at www.themotekpro.com for a period of 2 YEARS if used as directed and within the stated shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. Master Builders Solutions US MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is the replacement of product or refund of the purchase price, in the areas proven to have a product defect, at the sole option of Master Builders Solution US. Any claims concerning this product must be received in writing within two (2) years from the date of purchase and any claims not presented within that period are waived by Purchaser. Master Builders Solutions US WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND. The original proof of purchase must be provided.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions US present knowledge and experience. However, Master Builders Solutions US assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions US reserves the right to make any changes according to technological progress or further developments. The Purchaser of the product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

WARNING: Contains Titanium Dioxide, Limestone, Quartz, 2-Methylpropanoic acid monoester with 2,2,4-trimethylpentane-1,3 diol, Peroxisulfuric acid $[(HO)S(O)_2]_2O_2$ diammonium salt. MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED. MAY CAUSE ALLERGIC SKIN REACTION. MAY CAUSE CANCER BY INHALATION. Use only with adequate ventilation. Avoid breathing vapor. Avoid prolonged or repeated contact with skin and clothing. void contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container closed. IF INHALED: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Get medical attention. IF ON SKIN: In case of contact, remove contaminated clothing and shoes. Immediately flush skin with soap and plenty of water. Get medical attention if symptoms occur. IF IN EYES: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention if needed. IF SWALLOWED: Call a poison control center or physician immediately. DO NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person. KEEP OUT OF REACH OF CHILDREN. For additional information read the Safety Data Sheet (SDS) for this product.

 WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov